


Tri Clover Threaded Cap Reducer Series



Tri Clover Threaded Cap Reducer Series	Part		Thread	Pressure Rating	Temperature Range		Material
Product ID	TC	TC	NPS	PSI	°C	°F	Stainless Steel
ss-4TC-x-3TC-th-con-cap-reduce	4	3	2 1/2	300	-28 to 148	-20 to 300	304
ss-4TC-x-2.5TC-th-con-cap-re		2.5	2	300	-28 to 148	-20 to 300	304
ss-4TC-x-2TC-th-con-cap-reduce		2	1 1/2	300	-28 to 148	-20 to 300	304
ss-4TC-x-1.5TC-th-con-cap-re		1.5	1	300	-28 to 148	-20 to 300	304
ss-3TC-x-2.5TC-th-con-cap-re	3	2.5	2	300	-28 to 148	-20 to 300	304
ss-3TC-x-2TC-th-con-cap-reduce		2	1 1/2	300	-28 to 148	-20 to 300	304
ss-3TC-x-1.5TC-th-con-cap-re		1.5	1	300	-28 to 148	-20 to 300	304
ss-3TC-x-1TC-th-con-cap-reduce		1	1	300	-28 to 148	-20 to 300	304
ss-2.5TC-x-2TC-th-con-cap-red	2.5	2	1 1/2	300	-28 to 148	-20 to 300	304
ss-2.5TC-x-1.5TC-th-con-cap-re		1.5	1	300	-28 to 148	-20 to 300	304
ss-2.5TC-x-1TC-th-con-cap-re		1	1	300	-28 to 148	-20 to 300	304
ss-2TC-x-1.5TC-cap-1in-NHS	2	1.5	1	300	-28 to 148	-20 to 300	304
ss-2TC-x-1.5TC-th-con-cap-re		1.5	1	300	-28 to 148	-20 to 300	304
ss-2TC-x-1TC-th-con-cap-reduce		1	1	300	-28 to 148	-20 to 300	304
ss-1.5TC-x-3-4TC-th-con-cap-re	1.5	3/4	3/8	300	-28 to 148	-20 to 300	304
ss-1.5TC-x-1-2TC-th-con-cap-re		1/2	1/4	300	-28 to 148	-20 to 300	304
ss-1.5TC-x-1TC-th-con-cap-re		1	1	300	-28 to 148	-20 to 300	304